

Description

Manufacturing Standard : **BS EN 14411 : 2016**
 Manufacturing Process : Dry pressed & fired
 Product Type: Dry-pressed ceramic tiles, with water absorption Eb ≤ 0.5%
 Incorporates 20mm Porcelain Single Size Paving Tiles from Modena, Italy

Application: Domestic use only; hardstanding for pedestrian pavements including home patios, pathways and internal floor coverings. They are not designed for vehicular trafficking or commercial applications. (Please see www.brettpaving.co.uk for further guidance)

Product Performance

Strength Breaking Strength ≥ 11,000 N
 Resistance to Abrasion External 120-150 (≤175) Internal Class H
 Frost Resistance Pass - In accordance with EN ISO 10545-1
 Slipperiness >36 (36+ Low Slipping Risk) R values are not recognised in the UK but are available on request
 Reaction to fire Class A1 FL / A1
 Breaking Strength ≥11000 (≥1300 (thickness ≥7.5mm)
 Emission of asbestos No content
 Thermal Shock Resistance Complies with Standard EN 14411:2012

Dimensions (mm) & Typical Unit Weights (Kg)

Product	Size / Code	Working. Dims (mm)	Unit Weight (kg)
Elegante Porcelain 20mm Timber	1200x400	1195x396	22.99

Tolerance on Working Dimensions Thickness ±0.5mm; Plan Size ±2% (Max 5mm)
 Chamfer Straight Edge

Product Information

Design Standard n/a
 Installation Standard BS 5385-3:2014
 NBS Specification Not in NBS Library
 Colour Warm Oak
 Other Not applicable

<u>Product</u>	<u>Size</u>	<u>No. per pack</u>	<u>No. per m²</u>	<u>m² per pack</u>	<u>Pack Weight (kg)</u>	<u>Pack Type</u>
Elegante Porcelain 20mm Timber	1200x400	48	2.02	23.81	1103	Pallet

Useful Links

Brett Website - Domestic	https://www.brettpaving.co.uk/home-owners/porcelain-paving/elegante-porcelain/
Brett Website - Commercial	Not Applicable
NBS Specification	Not Applicable
BIM Model	Not Applicable
Cleaning & Maintenance	https://www.brettpaving.co.uk/knowledge-hub/maintenance-guides/

Contact Details

Telephone	0345 608 0570
E-Mail	project.designer@brett.co.uk