

GeoCeramica 40mm

Technical Data Sheet

Issue Ref: GC40:2 **Description** Manufacturing Standard : BS EN 1339 : 2003, BS EN 12004 : 2008, BS EN 1348 : 2007, BS EN 14411 : 2012 Manufacturing Process : Porcelain pre-bonded to no-fines concrete base. Product Type: Dry-pressed ceramic tiles, with a pre-bonded cementitious water permeable drainage layer. Incorporates 40mm GeoCeramica Fiordi, Irish Highstone Impasto, Marmostone & Mosaik from Nieuw-Lekkerland, Holland Application: Domestic use only; hardstanding for pedestrian pavements including home patios, pathways and internal floor coverings. They are not designed for vehicular trafficking or commerical applications. (Please see www.brettpaving.co.uk for further guidance) Product Performance Characteristic bending strength ≥ 5.0 Mpa / Characteristic breaking load > 4.5 KN Strength Layer Adhesion ≥ 0.5 N/mm² - Initial, after water saturation, after heat load ≥ 0.3 N/mm² - After freeze-thaw load Layer Adhesion Freeze Thaw Pass - Internal & External Freeze Thaw resistance Durability Slip / Skid Resistance >36 (36+ Low Slipping Risk) R values are not recognised in the UK but are available on request External Fire Performance Deemed to satisfy Emission of asbestos No content

Dimensions (mm) & Typical Unit Weights (Kg)

Product	Size / Code	Working. Dims (mm)	Unit Weight (kg)
Geoceramica 40mm Flag Paving	600x600	598x598	31.5

Tolerance on Working Dimensions	± 2mm on Thickness, Plan & Diagonals
Chamfer	Straight Edge
Product Information	
Design Standard	Please refer to Brett Technical Support
Installation Standard	BS 7533-4:2006
NBS Specification	45-80-95/310 Ceramic tiles / Q25 315
Colour	Grigio, Noir, Taupe, Black, Grey, Fumo, Sand, Gris Claro, Noir Puro, Dark Mist, Grey Mist
Other	Not applicable
Other	Not applicable

Product	Size	No. per pack	No. per m ²	m² per pack	Pack Weight (kg)	Pack Type		
Geoceramica 40mm Flag Paving	600x600	28	2.78	10.08	882	Pallet		
<u>Useful Links</u>								
Brett Website - Domestic Brett Website - Commercial	https://www.brettpaving.co.uk/home-owners/porcelain-paving/geoceramica/ https://www.brettpaving.co.uk/commercial/flag-paving/geoceramica-1/							
NBS Specification	Currently unavailable							
BIM Model	Currently unavailable							
Cleaning & Maintenance	https://www.brettpaving.co.uk/knowledge-hub/maintenance-guides/							
Contact Details								
Telephone	0345 608 0570							
E-Mail	project.designer@bre	<u>tt.co.uk</u>						