

Hague Antique Block Paving Technical Data Sheet



Dusk



Burnt Clay



Dusk



Stock Blend

Description

The Hague Antique Concrete Paving range flawlessly replicates the timeless look of traditional clay paviours with all the advantages of modern concrete technology. This premium paving solution combines classic elegance with durability, making it the perfect choice for those seeking to blend tradition with innovation. Hague Antique offers the same linear plan size as Hague Paving but has a traditional tumbled appearance. Available in three striking colour options.

Application

Hague Antique is suitable for most paving applications, ranging from small domestic and residential projects, to large urban and commercial installations.

Product Type	Precast Concrete Paving Blocks.
Manufacturing Process	Semi dry pressed & vibrated concrete.
Manufacturing Standard	BS EN 1338: 2003
Design Standard	BS 7533-101: 2021
Installation Standard	BS 7533-102: 2025
UKCA/DOP	<i>Contact Brett for more information</i>
NBS Specification	-

Product Performance

Nominal Dimensions (mm)	Working Dimensions (mm)	No.per pack	m2 per pack	No.per m2	Pack wt max kg
200x50x70	200x50x70	900	9	100	1042

Tolerances on Working Dimensions	Class 2 tolerances on dimensions, Plan Size \pm 2mm; Thickness \pm 3mm
Tensile Strength	Characteristic tensile splitting strength \geq 3.6 Mpa; Failing load \geq 250 N/mm
Abrasion Resistance	Class 4 - \leq 20mm - Determined by Wide Wheel Abrasion Test
Durability (Freeze Thaw)	Class 3 \leq 1,0kg/m ² with no individual result $>$ 1,5kg/m ²
Slip / Skid Resistance	PTV Unpolished Slip Resistance Value \geq 55 - Potential for slip - Low
Thermal Conductivity	Deemed to satisfy
Reaction to Fire	Class A1 when used for internal flooring
External Fire Performance	Deemed to satisfy

Sustainability

BREEAM	Concrete Block Paving 70-80mm: B rating, as per the BRE Green Guide, 4th Edition 2009, A rating can be achieved when used in conjunction with a prepared recycled sub-base.
BES 6001	Responsible Sourcing of Concrete Products (Rating: Excellent)
Recyclable	100% of this product can be recycled.
Embodied Carbon	<i>Contact Brett for more information</i>
Brett 5-Star Sustainability Rating	-

Early Life and Maintenance

Once your paving has been installed, you may notice some changes to its appearance in the first few days and weeks. These visual changes can be due to several reasons originating from the concrete and/or the manufacturing or installation method. Many of these will simply weather away, including:

Efflorescence	The ongoing chemical reaction within the concrete which provides its strength can produce calcium carbonate (a white powdery residue) which may appear on the surface of products. This temporarily lightens the product but will typically weather away without reoccurrence.
----------------------	--

Porosity

Concrete continues to cure for many years after manufacture. Whilst this happens and usually during its initial life, a level of porosity may exist where some product retains water, giving a damp appearance. This will diminish as the concrete continues to harden as the product dries out.

Aged and distressed products

For certain products, we distress the edges to offer an aged appearance and enhance the character of the paving. A dusty residue can be left on the blocks. This will weather away.

Differential Curing

Dark patches occasionally appear on the surface of concrete products. This may be differential curing and is caused by varying moisture levels within the flag drying at different rates. Like efflorescence, given time and the natural weathering process, these patches will become less visible.