ENVIRONMENTAL PRODUCT DECLARATION

as per ISO 14025 and EN 15804

Owner of the Declaration	British Precast Concrete Federation
Programme holder	Institut Bauen und Umwelt e.V. (IBU)
Publisher	Institut Bauen und Umwelt e.V. (IBU)
Declaration number	EPD-BPC-20170094-CCD1-EN
Issue date	26/07/2017
Valid to	25/07/2022

UK Manufactured 1 tonne of Generic Precast Concrete Paving Products (Blocks, Slabs, Channels and Kerbs) Produced by members of Interpave a product group of British Precast



www.ibu-epd.com / https://epd-online.com





General Information

British Precast Concrete Federation

Programme holder

IBU - Institut Bauen und Umwelt e.V. Panoramastr. 1 10178 Berlin Germany

Declaration number

EPD-BPC-20170094-CCD1-EN

This Declaration is based on the Product Category Rules:

Pre-cast concrete components, 07.2014 (PCR tested and approved by the SVR)

Issue date 26/07/2017

20/07/2017

Valid to 25/07/2022

Wermanes

Prof. Dr.-Ing. Horst J. Bossenmayer (President of Institut Bauen und Umwelt e.V.)

Dr. Burkhart Lehmann (Managing Director IBU)

Product

Product description / Product definition

The product covered in this EPD is a generic tonne of precast concrete paving products. The products covered are blocks, slabs, channels and kerbs. Concrete paving products are made of cement, aggregates, water and (if needed) admixtures. There are two main manufacturing processes for the paving block, paving flag and kerbs, dependent upon strength requirements. Paving flags can be produced by either casting into flexible silicon rubber or similar moulds or hydraulically pressed into a mould box. Paving blocks and other pressed products tend to be much dryer mixes and are predominantly produced from a blended dry mix. Once demoulded products are loaded into a curing chamber for accelerated curing or moved into the stockyard. Primary data for the production of precast concrete paving products were collected from members of Interpave. This data were used to generate a mass weighted average of production for the EPD.

For the placing on the market of the product in the EU/EFTA (with the exception of Switzerland) Regulation (EU) No. 305/2011 /CPR/ applies. The product needs a Declaration of Performance taking into consideration BS EN 1338:2003 concrete paving blocks, /BS EN 1339:2003/ concrete paving flags, /BS

Precast Concrete Paving Products

Owner of the Declaration

British Precast Ltd The Old Rectory 8 Main Street, Glenfield Leicester, LE38DG

Declared product / Declared unit

1 Tonne of Precast Concrete Paving Products (blocks, slabs, channels and kerbs)

Scope:

This is an association declaration which uses average data from member companies of Interpave to form an average tonne of precast concrete paving products. Concrete paving products include blocks, slabs, channels and Kerbs. It is based on data covering a period of 12 months (From January to December 2014). All data was collected from UK factories. The owner of the declaration shall be liable for the underlying information and evidence; the IBU shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

Verification

The CEN Norm /EN 15804/ serves as the core PCR Independent verification of the declaration according to /ISO 14025/

X

externally

internally

last-Otto

Mr Carl-Otto Neven (Independent verifier appointed by SVR)

EN 1340: 2003/ concrete kerb units and the CE marking. For the application and use the respective national provisions apply

Application

Precast concrete paving blocks and slabs are produced for both the domestic and commercial markets. Precast concrete paving products are used in a variety of paving applications including Sustainable Urban Drainage Systems (SUDS) and include blocks, slabs and kerbs.

Technical Data

Concrete paving products are manufactured to /BS EN 1338:2003/ Concrete paving blocks, /BS EN 1339:2003/ Concrete paving flags, /BS EN 1340:2003/ Concrete kerb units.



Constructional data

Name	Value	Unit
Gross density	2350	kg/m³
Dracking Strongth	Deemed to	
Breaking Strength	satisfy	
Slip/Skid Basistansa	Deemed to	
Silp/Skiu Resistance	satisfy	
	Deemed to	
Durability	satisfy	
Poaction to Fire	Deemed to	
	satisfy	
External Fire performance	Deemed to	
External File performance	satisfy	
Emission of ashestos	No content	

*Deemed to satisfy CE marking essential characteristic requirements. Performance data of the product in accordance with the Declaration of Performance with respect to its Essential Characteristics according to BS EN 1338:2003/ Concrete paving blocks, /BS EN 1339:2003/ Concrete paving flags, /BS EN 1340:2003/

LCA: Calculation rules

Declared Unit

The declared unit is 1 Tonne of Precast Concrete Paving Products. The data used in the LCA calculations is an average based on total annual production figures from members of Interpave. The declared unit includes a range of different products including paving blocks, paving slabs, channel products and kerbs. Information on assumed density and other physical characteristics are shown in the table below.

Declared unit

Name	Value	Unit
Density	2350	kg/m ³
Declared unit	1	t

System boundary

Type of EPD: Cradle to Gate with all options declared. The modules considered in the Life Cycle Assessment are modules A1-C4 inclusive.

Environment and health during manufacturing

Members of Interpave have formal Environmental Management Systems to put in place environmental protection measures which extend beyond national guidelines. At the time of publication 100% of sites providing data have a certified ISO14001 EMS.

Packaging

The amount and type of packaging used on precast concrete paving products will vary dependant on specific requirements. In a proportion of cases product will need no packaging other than banding and pallets for transportation. In other circumstances, the product will be stacked, banded, shrink-wrapped and placed on pallets for transportation.

Re-use phase

The durability of precast concrete paving products means that in the majority of cases a large proportion of an installation would be suitable for reuse whether it is relayed after settling and levelling procedures have taken place or used in other locations without the need to recycle or downgrade the product. This re-use Concrete kerb units.

To get accurate constructional data obtain a declaration of performance from your Interpave supplier.

Base materials / Ancillary materials

The concrete mix proportions are as follows: aggregates 84% cement 11%; PFA 1% GGBS 1% water 3%. The mix also contains admixtures and pigment.

No /REACH/ substances of very high concern are included.

Reference service life

/BS 8500/, the UK's concrete specification standard complementary to EN206, sets durability requirements for precast concrete elements. The reference service life (RSL) for the declared unit is 50 years.

should be considered when assessing the environmental credentials of the product but is not formally modelled in this study.

Cut-off criteria

/EN 15804/ requires that where there are data gaps or insufficient input data for a unit process the cut-off criteria shall be 1% of renewable and non-renewable primary energy usage and 1% of the total mass of this unit process. The total neglected flows from a product stage must be no more than 5% of product inputs by mass or 5% of primary energy contribution. In this assessment, all information gathered from data collection for the production of precast concrete has been modelled, i.e. all raw materials used, the electrical energy and other fuels used, use of ancillary materials and all direct production waste. Transport data on input and output flows are also considered. Scenarios have been developed to account for downstream processes such as fabrication, installation, demolition and waste treatment. No cutoffs have been made. Hence this study complies with the cut-off criteria defined in the /PCR/.

Background data

Background data is based primarily on a generic dataset /GaBi ts 2014 software database/ integrated into the IBU verified bespoke British Precast Envision EPD tool. The background data also includes UK specific cement data supplied by members of the Mineral Products Association (MPA). (Tool Verified 07/03/17).

Allocation

All allocation is performed according to the PCR. As no co-products are produced, the flow of materials and energy and also the associated release of substances and energy into the environment are related exclusively to the concrete produced.

British Precast



((mpa British Precast

Comparability

Basically, a comparison or an evaluation of EPD data is only possible if all the data sets to be compared were created according to /EN 15804/ and the building

context, respectively the product-specific characteristics of performance, are taken into account.

LCA: Scenarios and additional technical information

The following information supports the declaration of modules A1-C4 inclusive.

Transport to the building site (A4)

Name	Value	Unit
Transport distance	94.3	km
Capacity utilisation (including empty	50	0/2
runs)	50	70

Installation into the building (A5)

value	Unit
3	%
	3

Use or application of the installed product (B1)

In practice, given the nature of the product and its application in the structure of the built asset, no impacts are associated with the use stage of paving over the lifetime of the asset. However, carbonation of concrete will occur during the lifetime of the asset and is included in module B1. Carbonation is calculated using the approach recommended by the Mineral Products Association and BPCF and follows the methodology developed by Pommer et al. /Pommer 2005/, with reference to the work of Engelsen and Justnes /Engelsen 2014/, who have made further refinements related to the amount of CaO that can carbonate and the carbonation of slag.

For precast concrete carbonation factors based on BPCF research and expert judgement have been used. The surface area is assumed to be 6.84m² based on one exposed surface for an average paving installation.

The study period is assumed to be 50 years (the RSL).

Modules B2 - B7 (Maintenance, Repair, Replacement, Refurbishment, Operational Energy Use, Operational Water Use)

It is assumed that the precast concrete paving products covered by this EPD do not require maintenance, repair, replacement or refurbishment during their lifetime. Consequently, the impacts associated with these lifecycle stages are zero. There is no operational energy or operational water requirement associated with the product.

Reference service life

Name	Value	Unit
Reference service life	50	а

End of life (C1-C4)

Name	Value	Unit
Recycling	90	%
Landfilling	10	%

(MPPa British Precast

LCA: Results

In Table 1 "Description of the system boundary", all declared modules are indicated with an "X"; Module D which is not declared is indicated with "MND". Indicator values are declared to three valid digits. DESCRIPTION OF THE SYSTEM BOUNDARY (X = INCLUDED IN LCA: MND = MODULE NOT DECLARED)

PROE	OUCT S	TAGE	CONS ON PF ST	TRUCTI ROCESS AGE		USE STAGE END OF LIFE STAGE BEYOND T SYSTEM BOUNDAR					END OF LIFE STAGE				ITS AND ADS ND THE STEM DARIES		
Raw material supply	Transport	Manufacturing	Transport from the gate to the site	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment Onerational energy	Occupied under		De-construction	Transport	Waste processing	Disposal	Reuse- Recoverv-	Recycling- potential
A1	A2	A3	A4	A5	B1	B2	В3	B4	B5 E	36	B7	C1	C2	C3	C4		D
х	Х	Х	X	X	Х	Х	X	Х	x	x	Х	Х	X	X	X	M	ND
RESU	ILTS	OF TH	HE LC	A - EN'	VIRON	MENT	AL IMP	ACT: 1	tonne	of Pa	aving	J Pro	oducts		1		
Param eter	U	nit	A1-A3	3 A4	A5	B1	B2	B3	B4	B5	1	B6	B7	C1	C2	СЗ	C4
GWP	[kg CC	D ₂ -Eq.]	131.00) 6.62	1.00	-4.42	0.00	0.00	0.00	0.00) 0	.00	0.00	-0.43	3.46	-1.60	1.31
ODP	[kg CFC	211-Eq.]	9.26E-	7 4.48E-1	2 4.82E-1	12 0.00E+	0 0.00E+	0 0.00E+0	0.00E+	0 0.00E	+0 0.0	0E+0	0.00E+0	0.00E+0	2.34E-12	2.46E-11	1.78E-11
EP	[kg (PO	<u>⁄₂-⊏q.j</u>)₄) ³⁻ -Eq.]	2.37E-	2 6.76E-	2 0.24E- 3 1.55E-	4 0.00E+	0 0.00E+	0 0.00E+0	0.00E+	0 0.00E	+0 0.0	0E+0	0.00E+0	0.00E+0	3.54E-3	3.95E-3	9.03E-3
POCP	[kg ethe	ene-Eq.]	7.06E-	2 -1.03E-	2 9.40E-	5 0.00E+	0 0.00E+	0 0.00E+(0.00E+	0 0.00E	+0 0.0	0E+0	0.00E+0	0.00E+0	-5.41E-3	2.39E-3	9.25E-4
	[kg Sl	b-Eq.]	2.75E-	4 1.24E-	7 2.04E-	7 0.00E+	0 0.00E+	0 0.00E+0	0.00E+	0 0.00E	+0 0.0	0E+0	0.00E+0	0.00E+0	6.50E-8	4.21E-6	5.54E-7
Caption	ADP+ [MJ] 819.00 91.10 2.13 0.00 0.00 0.00 0.00 0.00 0.00 0.00 44.90 20.90 GWP = Global warming potential; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential of land and water; EP = Eutrophication potential; POCP = Formation potential of tropospheric ozone photochemical oxidants; ADPE = Abiotic depletion potential for non-fossil resources; ADPF = Abiotic depletion potential for fossil resources																
RESU	ILTS	OF TH	HE LC	A - RE	SOUR	CE USI	E: 1 tor	nne of l	Paving	Prod	ucts						
_	tor I	Jnit	A1-A3	A4	A5	B1	B2	B3	B4	B5	В	6	B7	C1	C2	C3	C4
Parame					0.00	0.00	0.00	0.00	0.00	0.00	0.0	00	0.00	0.00	0.00	0.00	0.00
Parame		MJ]	125.00	0.00	0.00	0.00	0.00	0 00	0.00	0.00	0	n n			0.00	0.00	0.00
Parame PERI PERI PER		MJ] MJ] MJ1	125.00 0.00 125.00	0.00 0.00 1.85	0.00	0.00	0.00	0.00	0.00	0.00	0.0	00	0.00	0.00	0.00 0.97	0.00	0.00
Parama PERI PERI PERI PENR	E [M [T [E [MJ] MJ] MJ] MJ]	125.00 0.00 125.00 896.00	0.00 0.00 1.85 0.00	0.00 0.20 0.00	0.00 0.00 0.00	0.00 0.00 0.00	0.00 0.00 0.00	0.00 0.00 0.00	0.00 0.00 0.00	0.0	00 00 00	0.00 0.00 0.00	0.00 0.00 0.00	0.00 0.97 0.00	0.00 3.46 0.00	0.00 0.00 2.46 0.00
Parame PERI PERI PERR PENR	E [M [T [E [M [MJ] MJ] MJ] MJ] MJ]	125.00 0.00 125.00 896.00 0.00	0.00 0.00 1.85 0.00 0.00	0.00 0.20 0.00 0.00	0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00	0.0	00 00 00 00	0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00	0.00 0.97 0.00 0.00	0.00 3.46 0.00 0.00	0.00 0.00 2.46 0.00 0.00
Parame PERI PERI PERI PENR PENR PENR	E [M [T [RE [M [RT]	MJ] MJ] MJ] MJ] MJ] MJ]	125.00 0.00 125.00 896.00 0.00 896.00 54.90	0.00 0.00 1.85 0.00 0.00 91.30 0.00	0.00 0.20 0.00 0.00 2.28 0.00	0.00 0.00 0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00 0.00	0.0	00 00 00 00 00 00	0.00 0.00 0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00 0.00	0.00 0.97 0.00 0.00 47.70 0.00	0.00 3.46 0.00 0.00 46.00	0.00 0.00 2.46 0.00 0.00 21.60 0.00
Parame PERI PERI PENR PENR PENR SM RSF	E [M [T [RE [M [RT [MJ] MJ] MJ] MJ] MJ] MJ] Kg] MJ]	125.00 0.00 125.00 896.00 0.00 896.00 54.90 0.00	0.00 0.00 1.85 0.00 0.00 91.30 0.00 0.00	0.00 0.20 0.00 0.00 2.28 0.00 0.00	0.00 0.00 0.00 0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00 0.00 0.00 0.00	0.0 0.0 0.0 0.0 0.0 0.0	00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00	0.00 0.00 0.00 0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00 0.00 0.00 0.00	0.00 0.97 0.00 47.70 0.00 0.00	0.00 3.46 0.00 0.00 46.00 0.00 0.00	0.00 0.00 2.46 0.00 0.00 21.60 0.00 0.00
Perame PERI PERI PERI PENR PENR SM RSF	E [] M [] T [] RE [] M [] M [] F []	MJ] MJ] MJ] MJ] MJ] MJ] kg] MJ] MJ] MJ] m ³	125.00 0.00 125.00 896.00 0.00 896.00 54.90 0.00 0.00 1.97E-1	0.00 0.00 1.85 0.00 91.30 0.00 0.00 0.00 0.00 5.93E-2	0.00 0.20 0.00 2.28 0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.0	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.0	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.0	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.0	0.00 0.00 0.00 0.00 0.00 0.00 0.00		00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.0	0.00 0.97 0.00 47.70 0.00 0.00 0.00 3.10E-3	0.00 3.46 0.00 0.00 46.00 0.00 0.00 0.00 1.20E-2	0.00 0.00 2.46 0.00 21.60 0.00 0.00 0.00 0.00 4.41E-3
Parame PERI PERI PENR PENR PENR SM RSF NRSS FW	E [M] T [E [M] T [T] T [T] T [T] T] T [T] T] T] T [T] T] T] T] T] T] T] T]	MJ MJ MJ MJ MJ MJ MJ MJ MJ MJ ERE = vable p on-rene wable p condar	125.00 0.00 125.00 896.00 0.00 896.00 54.90 0.00 1.97E-1 Use of r primary e ewable p primary e y materi	0.00 0.00 1.85 0.00 91.30 0.00 91.30 0.00 0.00 5.93E-3 renewable nergy re- primary et energy re- at, RSF =	0.00 0.20 0.20 0.00 2.28 0.00 0.00 2.79E-3 e primary sources bargy exits sources Use of the sources Sources of th	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.0	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.0	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00E+0 renewab rials; PER rials; PER rials; PER rials; PER rials; PEN	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00E+0 0.00E+0 0.00E+0 0.00E+0 0.00E+0 0.00E+0 0.00E+0 0.00E+0 0.00E+0 0.0	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.0	0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0	00 00 00 00 00 00 00 00 00 E+0 00 00 00 00 00 00 00 00 00	0.00 0.00	0.00 0.00	0.00 0.97 0.00 47.70 0.00 0.00 0.00 3.10E-3 terials; P esources; PENRM ergy resc els; FW =	0.00 3.46 0.00 0.00 46.00 0.00 0.00 0.00 1.29E-2 ERM = U PENRE = Use of purces; S = Use of p	0.00 0.00 2.46 0.00 0.00 21.60 0.00 0.00 0.00 0.00 0.00 4.41E-3 se of = Use of non- M = Use het fresh
Parame PERI PERI PENR PENR PENR SM RSF NRSI FW Caption	E I M I T I RE I M I F I F I renev n renev of se ILTS (n	MJ MJ MJ MJ MJ MJ MJ MJ MJ MJ ERE = vable p on-rene condar OF TH Pavir	125.00 0.00 125.00 896.00 0.00 896.00 54.90 0.00 0.00 1.97E-1 Use of r rimary e ewable p primary e trimary	0.00 0.00 1.85 0.00 0.00 91.30 0.00 0.00 0.00 5.93E-3 renewable energy reaction of the second se	0.00 0.00 0.20 0.00 0.00 2.28 0.00 0.00 0.00 2.79E-3 e primary sources to hergy exists sources to the primary sources to the primary sources to the primary to the primary sources to the primary sources to the primary to the primary sources to the primary to the primary sources to the primary to the primary to the primary sources to the primary to the primary to the primary to the primary sources to the primary	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00E+0 v energy used as r cluding n used as r enewabl FLOW	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00E+0 excluding aw mater on-renew raw mate e second S AND	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00E+0 renewab ials; PER rable prim rials; PEN ary fuels; WAST	0.00 0.00	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.0	0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0	00 00 00 00 00 00 00 00 00 00	0.00 0.00	0.00 0.00	0.00 0.97 0.00 47.70 0.00 0.00 0.00 3.10E-3 terials; P sources; PENRM ergy resc els; FW =	0.00 3.46 0.00 0.00 0.00 0.00 0.00 0.00 1.29E-2 ERM = U PENRE = Use of purces; S = Use of n	0.00 0.00 2.46 0.00 0.00 21.60 0.00 0.00 4.41E-3 se of = Use of non- M = Use net fresh
Parame PERI PERI PERI PENI PENI PENI SM RSF NRSI FW Caption 1 ton Parame	E I M I T I BE I M I T I RT I F I F I renew n renew of se ILTS I Deter I	MJ MJ MJ MJ MJ MJ MJ MJ ERE = wable p on-rene wable p condar OF TH Pavir Jnit	125.00 0.00 125.00 896.00 0.00 54.90 0.00 1.97E-1 Use of rominary eportmany ep	0.00 0.00 1.85 0.00 91.30 0.00 91.30 0.00 0.00 0.00 5.93E-3 renewable energy re- al; RSF = A – OL ducts A4	0.00 0.20 0.00 0.00 2.28 0.00 0.00 2.79E-3 e primary sources the regy exx. sources the sources the sou	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00E+0 7 energy used as r cluding n used as l renewabl FLOW B1	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 excluding aw mater on-renew raw mate e second S AND B2	0.00 0.00 0.00 0.00 0.00 0.00 0.00E+0 renewab rials; PER rials; PER rials; PER ary fuels; WAST B3	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00E+0 0.00E+0 0.00E+0 0.00E+T = Tota ary ener IRT = Tota NRSF = water E CAT B4	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.0	0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0	00 00 00 00 00 00 00 00 00 00	0.00 0.00	0.00 0.00	0.00 0.97 0.00 47.70 0.00 0.00 0.00 0.00 3.10E-3 terials; Pl sources; PENRM ergy resc els; FW =	0.00 3.46 0.00 0.00 46.00 0.00 0.00 0.00 1.29E-2 ERM = U PENRE = Use of I Use of I	0.00 0.00 2.46 0.00 0.00 21.60 0.00 0.00 0.00 4.41E-3 se of = Use of non- M = Use net fresh
Parame PERI PERI PERR PENR PENR PENR SM RSF NRSI FW Caption 1 ton Parame HWE	E [M [M [M [RT [F [P renevon renevon no renevon no ne of se JLTS (ster [p [MJ MJ MJ MJ MJ MJ MJ m ³ ERE = vable p on-rene wable p condar OF TH Pavin Jnit kg	125.00 0.00 125.00 896.00 0.00 54.90 0.00 1.97E-1 Use of rominary e wable porimary e y materi HE LC 1g Pro A1-A3 1.63E-2	0.00 0.00 1.85 0.00 91.30 0.00 91.30 0.00 0.00 0.00 0.00 5.93E-3 enerwable energy real; RSF = A – OL ducts A4 4.25E-7	0.00 0.20 0.00 0.228 0.00 0.00 2.28 0.00 0.00	0.00 0.00	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 excluding aw mater on-renew raw mate e second S AND B2 0.00E+0	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 renewab ials; PER able prim rials; PEN ary fuels; WAST B3 0.00E+0	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00E+0 0.00E+0 0.00E+0 NRSF = water E CAT B4 0.00E+0	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.0	0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0 0.0 0 0.0 0 0 0.0 0 0 0.0 0 0 0.0 0 0 0.0 0 0 0.0 0 0 0.0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	20 20 20 20 20 20 20 20 20 20	0.00 0.00	0.00 0.00	0.00 0.97 0.00 0.00 47.70 0.00 0.00 0.00 3.10E-3 terials; PI sources; PENRM ergy resc els; FW = C2 2.22E-7	0.00 3.46 0.00 0.00 46.00 0.00 0.00 1.29E-2 ERM = U PENRE = Use of 1 Durces; S = Use of 1 C3 3.28E-6	0.00 0.00 2.46 0.00 0.00 21.60 0.00 0.00 4.41E-3 se of = Use of non- M = Use net fresh C4 4.94E-7
Parame PERI PERI PERI PENI PENI SM RSF NRSI FW Caption 1 ton Parame HWC	E [M [M [RT [F [F [P renew n renew of se [JLTS [D [MJ MJ MJ MJ MJ MJ MJ MJ ERE = wable p condar OF TH Pavin Jnit kg	125.00 0.00 125.00 896.00 0.00 54.90 0.00 1.97E-1 Use of romary events of romary ev	0.00 0.00 1.85 0.00 0.00 91.30 0.00	0.00 0.00 0.20 0.00 0.00 2.28 0.00 0.00 2.79E-3 e primary sources the primary sour	0.00 0.00	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 excluding aw mate e second S AND B2 0.00E+0 0	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 renewab ials; PER able prim rials; PEN ary fuels; WAST B3 0.00E+0 0.00E+0	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00E+0 0.00E+0 0.00E+0 Water E CAT B4 0.00E+0 0.00E+0	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 1 use of gy reso tal use Use of EGOI B5 0.00E+ 0.00E+	0.000000000000000000000000000000000000	200 200 200	0.00 0.00	0.00 0.00	0.00 0.97 0.00 0.00 47.70 0.00 0.00 0.00 3.10E-3 terials; PI securces; PENRM ergy resc els; FW = 2.22E-7 8.35E-4 -4.55E-4	0.00 3.46 0.00 0.00 0.00 0.00 0.00 1.29E-2 ERM = U PENRE = Use of n Use of n 0.00 0.00 1.29E-2 3.28E-6 2.18E-2 1.45E-2	0.00 0.00 2.46 0.00 0.00 21.60 0.00 4.41E-3 se of = Use of non- M = Use of non- M = Use t fresh C4 4.94E-7 1.00E+2
Parame PERI PERI PERI PENR PENR PENR SM RSF NRSI FW Caption RESU 1 ton Parame HWD NHW RWD CRU	E I M I T I E I M I T I RT I F I F I I I renew n renew n renew n ILTS (I D I D I D I	MJ MJ MJ MJ MJ MJ MJ MJ MJ MJ	125.00 0.00 125.00 896.00 0.00 54.90 0.00 1.97E-1 Use of r rimary e wable p primary e wable p rimary e the LC 1.97E-1 1.97E-1 1.63E-2 3.77E+1 3.12E-2 0.00	0.00 0.00 1.85 0.00 91.30 0.00 91.30 0.00 0.00 5.93E-3 renewable energy res- primary energy res- primary energy res- primary energy res- the energy res- primary energy res- the energy res- 0.00 0.0	0.00 0.00 0.20 0.00 2.28 0.00 0.00 2.79E-3 e primary sources the rergy exists sources the rergy	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00E+0 venewabl FLOW B1 0.00E+0	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00E+0 e second S AND B2 0.00E+0	0.00 0.00	0.00 0.00	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.0	0.0.0 0.0.0 0.0.0 0.0.0 0.0.0 0.0.0 0.0.0 0.0.0 0.0.0 0 0.0 0 0.0 0 0.0 0 0.0 0 0 0.0 0 0 0.0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200	0.00 0.00	0.00 0.00	0.00 0.97 0.00 0.00 47.70 0.00 0.00 0.00 3.10E-3 terials; PENRM ergy resc els; FW = 2.22E-7 8.35E-4 5.12E-5 0.00	0.00 3.46 0.00 0.00 46.00 0.00 0.00 0.00 1.29E-2 ERM = U PENRE = Use of purces; S 1.28E-0 1.28E-2 4.47E-4 0.00	0.00 0.00 2.46 0.00 0.00 21.60 0.00 0.00 4.41E-3 se of = Use of non- M = Use of non- M = Use t fresh C4 4.94E-7 1.00E+2 3.02E-4 0.00
Parame PERI PERI PENR PENR PENR SM RSF NRSI FW Caption RESU 1 toni Parame HWD NHW RWD CRU	E I M I T I E I M I E I M I RT I F I F I I I F I I I I I I I I I I I I I D I D I I I R I	MJ MJ MJ MJ MJ MJ MJ MJ MJ ERE = wable p on-rene wable p condar OF TH Pavir Jnit kg kg kg kg	125.00 0.00 125.00 896.00 0.00 54.90 0.00 1.97E-1 Use of r rimary e ewable p orimary e y materi HE LC 1.63E-2 3.77E+1 3.12E-2 0.00 0.00	0.00 0.00 1.85 0.00 91.30 0.00 91.30 0.00 0.00 5.93E-3 renewable energy reaction of the second primary eternergy reaction of the second energy	0.00 0.00 0.20 0.00 2.28 0.00 0.00 2.79E-3 e primary sources the primary sources the sources the sourc	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00E+0 / energy / used as r cluding n used as r cluding n used as r cluding n 0.00E+0	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00E+0 excluding aw mater on-renew aw mater e second S AND B2 0.00E+0	0.00 0.00	0.00 0.00	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.0	0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0.0 0.0.0 0.0.0 0.0.0 0.0.0 0.0.0 0.0.0 0.0.0 0.0.0 0.0.0 0.0.0	200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200	0.00 0.00	0.00 0.00	0.00 0.97 0.00 47.70 0.00 0.00 0.00 3.10E-3 terials; P PENRM PENRM PENRM 2.22E-7 8.35E-4 5.12E-5 0.00 0.00 0.00	0.00 3.46 0.00 0.00 46.00 0.00 0.00 1.29E-2 ERM = U PENRE = Use of the second secon	0.00 0.00 2.46 0.00 0.00 21.60 0.00 0.00 4.41E-3 se of = Use of non- M = Use of tresh C4 4.94E-7 1.00E+2 3.02E-4 0.00
Parame PERI PERI PENR PENR PENR SM SM SM SM SM SM SM SM SM SM SM SM SM	E I M I T I E I M I T I E I M I T I E I M I T I E I F I F I F I I F I I P renevon n renevon n renevon D I D I I I R I	MJ MJ MJ MJ MJ MJ MJ MJ ERE = wable p condar Pavir Jnit kg kg kg kg kg	125.00 0.00 125.00 896.00 0.00 896.00 0.00 1.97E-1 Use of rorimary e ewable porimary e ey materi HE LC 1.63E-2 3.77E+1 3.12E-2 0.00 0.00 0.00 0.00 0.00 0.00	0.00 0.00 1.85 0.00 91.30 0.00 91.30 0.00 0.00 5.93E-3 renewable energy reaction of the second primary elemergy reaction of the second energy	0.00 0.00 0.20 0.00 0.00 2.28 0.00 0.00 0.00 0.00 0.00 2.79E-3 e primary sources the sources the source the source the source the source the sources t	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 FLOW B1 0.00E+0 0.00E	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 Excluding aw mate on-renew aw mate e second S AND B2 0.00E+0	0.00 0.00	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 E CAT B4 0.00 E CAT B4 0.00	0.00 0.00 0.00 0.00 0.00 0.00 0.00E 1 use of gy reso tal use of gy reso tal use of EGOI B5 0.00E+ 0.00E+ 0.00E+ 0.00E	0.000000000000000000000000000000000000	200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200	0.00 0.00	0.00 0.00	0.00 0.97 0.00 47.70 0.00 0.00 0.00 3.10E-3 terials; P esources; PENRM ergy resc els; FW = 2.22E-7 8.35E-4 5.12E-5 0.00 0.00 0.00 0.00	0.00 3.46 0.00 0.00 46.00 0.00 0.00 1.29E-2 ERM = U PENRE Use of r Use of r Use of r 0.00 2.18E-2 4.47E-4 4.47E-4 0.00 873.00 0.00 0.00	0.00 0.00 0.00 2.46 0.00 2.46 0.00 0.00 21.60 0.00 0.00 0.00 0.00 0.00 4.41E-3 se of = Use of non- M = Use of non- M = Use of net fresh 1.00E+2 3.02E+4 0.00 0.00 0.00
Parame PERI PERI PERI PENI PENI PENI SM RSF NRSI FW Caption 1 ton 1 ton Parame HWL NHW RWL CRL MFF MEF EEE	E I Image: Image and the second	MJ MJ MJ MJ MJ MJ MJ MJ ERE = vable p on-rene wable p condar OF Th Pavin Jnit kg Xg kg kg kg Kg MJ MJ	125.00 0.00 125.00 896.00 0.00 54.90 0.00 1.97E-1 Use of rorimary erewable por washer por year of the second seco	0.00 0.00 1.85 0.00 0.00 91.30 0.00 0.00 0.00 5.93E-3 enewable energy rea- primary ele- energy rea- al; RSF = A - OL ducts A4 4.25E-7 1.60E-3 9.79E-5 0.00 0.0	0.00 0.00 0.20 0.00 0.00 2.28 0.00 0.00 0.00 0.00 0.00 2.79E-3 e primary sources the sources the source th	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 FLOW B1 0.00E+0	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 B2 0.00E+0 0.000E+0	0.00 0.00	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 E CAT B4 0.00E+0	0.00 0.00 0.00 0.00 0.00 0.00 0.00 1 use of gy reso tal use Use of EGOI B5 0.00E+ 0.00E+ 0.00E+ 0.00E+ 0.00E+	0.0.0 0.0.00 0.0.00 0.0.00 0.0.000000	200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200 200	0.00 0.00	0.00 0.00	0.00 0.97 0.00 47.70 0.00 0.00 0.00 3.10E-3 terials; Pl sources; PENRM ergy resce els; FW = C2 2.22E-7 8.35E-4 5.12E-5 0.00 0.00 0.00 0.00	0.00 3.46 0.00 0.00 46.00 0.00 0.00 1.29E-2 ERM = U PENRE = Use of 1 Use of 1 3.28E-6 2.18E-2 4.47E-4 0.00 873.00 0.00 0.00 0.00	0.00 0.00 0.00 2.46 0.00 2.46 0.00 2.46 0.00 0.00 21.60 0.00 0.00 0.00 0.00 0.00 4.41E-3 se of = Use of non-M = Use of non-M M = Use of tresh 1.00E+2 3.02E-4 0.00 0.00 0.00 0.00 0.00



Interpretation

Interpretation of the results has been carried out considering the methodology, data-related assumptions and any limitations declared in the EPD.

Interrogation of the LCA results show that the cradle-to-grave **GWP** (Global Warming Potential) impact of 1 tonne of paving products is 136.9 kgCO2e (Modules A1-C4).

For **GWP**, A1-A3 accounts for 96% of the lifecycle impact with carbonation in the use phase and post-demolition, reducing the overall impact of paving products. Carbonation in the use phase alone reduces the **GWP** impact by 3%.

The LCA results show that the cradle-to grave-primary energy demand of the declared unit is 1239 MJ (Modules A1-C4).

Analysis of the **PERT/ PENRT** (Total use of renewable primary energy resources/ Total use of non-renewable primary energy resources) figures show the largest contributors are cement 37(%), transport 16(%) and utilities used in production 14(%).

For primary energy demand, A1-A3 accounts for 82% of the lifecycle impact.

The cradle to grave Net use of fresh water (**FW**) is 0.23m3 (Modules A1-C4) with the product stage (A1-A3) accounting for 87% of this.

References

Institut Bauen und Umwelt

Institut Bauen und Umwelt e.V., Berlin(pub.): Generation of Environmental Product Declarations (EPDs); www.ibu-epd.de

ISO 14025

DIN EN ISO 14025:2011-10: Environmental labels and declarations — Type III environmental declarations — Principles and procedures

EN 15804

EN 15804:2012-04+A1 2013: Sustainability of construction works — Environmental Product Declarations — Core rules for the product category of construction products

PCR Part A

Institut Bauen und Umwelt e.V., Berlin (pub.): Product Category Rules for Construction Products from the range of Environmental Product Declarations of Institut Bauen und Umwelt (IBU), Part A: Calculation Rules for the Life Cycle Assessment and Requirements on the Background Report. April 2013

PCR Part B

Part B: Requirements on the EPD for Pre-cast concrete components, Version 1.6, *Institut Bauen und Umwelt* e.V., www.bau-umwelt.com, 2014

EN ISO 14040

EN ISO 14040:2006 Environmental management - Life cycle assessment - Principles and framework

EN ISO 14044

EN ISO 14044:2006 Environmental management - Life cycle assessment - Requirements and guidelines.

EN 206

BS EN 206:2013: Concrete. Specification, performance, production and conformity

EN 1338

BS EN 1338:2003 Concrete paving blocks.

EN 1339

BS EN 1339:2003 Concrete paving flags.

EN 1340

BS EN 1340:2003 Concrete kerb units.

EU No 305/2011

Regulation (EU) No 305/2011 - construction products regulation

BS 8500

BS 8500-1:2015: Concrete. Complementary British Standard to BS EN 206. Method of specifying and guidance for the specifier.

Engelsen 2014

Engelsen, C. and Justnes, H. (2014) CO2 binding by concrete - Summary of the state of the art and an assessment of the total binding of CO2 by carbonation in the Norwegian concrete stock. SINTEF Building and Infrastructure, Oslo, Norway.

Pommer 2005

Pommer, K. and Pade, C (2005) Guidelines - Uptake of carbon dioxide in the life cycle inventory of concrete. Danish Technological Institute, Copenhagen, Denmark

thinkstep

GaBi ts 2014 software database

Institut Bauen und Umwelt e.V.	Publisher Institut Bauen und Umwelt e.V. Panoramastr. 1 10178 Berlin Germany	Tel Fax Mail Web	+49 (0)30 3087748- 0 +49 (0)30 3087748- 29 info@ibu-epd.com www.ibu-epd.com
Institut Bauen und Umwelt e.V.	Programme holder Institut Bauen und Umwelt e.V. Panoramastr 1 10178 Berlin Germany	Tel Fax Mail Web	+49 (0)30 - 3087748- 0 +49 (0)30 – 3087748 - 29 info@ibu-epd.com www.ibu-epd.com
British Precast	Author of the Life Cycle Assessment British Precast Concrete Federation (BPCF) The Old Rectory, Main Street 8 LE38DG Glenfield United Kingdom	Tel Fax Mail Web	01162325170 01162325197 info@britishprecast.org www.britishprecast.org
thinkstep	thinkstep Ltd Electric Works, Sheffield Digital, Campus 1 . S1 17L Sheffield United Kingdom	Tel Fax Mail Web	0114 286 6336 0114 286 6201 alex.hardwick@thinkstep.com info@thinkstep.com
Interpave Net Parcent for Aller Annog AND KERS ABSOCIATION	Owner of the Declaration Interpave The Old Rectory, Main Street 8 LE38DG Glenfield United Kingdom	Tel Fax Mail Web mme l	01162325170 01162325197 info@britishprecast.org http://www.paving.org.uk/co rcial/index.php
British Precast	British Precast Concrete Federation (BPCF) The Old Rectory, Main Street 8 LE38DG Glenfield United Kingdom	Tel Fax Mail Web	01162325170 01162325197 info@britishprecast.org www.britishprecast.org