

# Elegante Quartz 900x600mm Porcelain Paving

## Technical Data Sheet



Antique Greige



Antique Greige

### Description

Featuring a distinct, fine veined texture, Brett Elegante Quartz porcelain paving offers contemporary looks combined with the practicalities of porcelain paving. The 900 x 600mm Quartz Antique Greige has the beautiful texture of quartz with blended, bronzed tones.

### Application

Brett Elegante Quartz Porcelain has been designed for domestic use, including patios, pathways and internal floor coverings. It isn't recommended for use in vehicular trafficking applications.

<b>Product Type</b>	Dry-pressed ceramic tiles
<b>Manufacturing Process</b>	Dry pressed and fired.
<b>Manufacturing Standard</b>	BS EN 14411:2016
<b>Design Standard</b>	-
<b>Installation Standard</b>	BS 7533-102: 2025
<b>UKCA/DOP</b>	Contact Brett for more information
<b>NBS Specification</b>	-

## Product Performance

Nominal Dimensions (mm)*	Working Dimensions (mm)	No. per pack	m2 per pack	No. per m2	Pack wt max kg
900x600x20	900x600x20	48	26.28	1.83	1200

<b>Tolerances</b>	Thickness $\pm 0.5\text{mm}$ Plan Size $\pm 0.6\%$ (Max $\pm 2\text{mm}$ )
<b>Breaking Strength</b>	Average Breaking Strength $\geq 9,000\text{ N}$
<b>Abrasion Resistance</b>	Class 4 – In accordance with EN ISO: 10545-7
<b>Staining Resistance</b>	Class 5 – In accordance with EN ISO: 10545-14
<b>Frost Resistance</b>	Pass – In accordance with EN ISO 10545-12
<b>Slip / Skid Resistance</b>	$>36$ (36+ Low Slipping Risk) R values are not recognised in the UK but are available on request
<b>Reaction to Fire</b>	Class A1 FL / A1
<b>Average Modulus of Rupture</b>	$\geq 35\text{ N/mm}^2$
<b>Water absorption</b>	$\leq 0.5\%$

## Sustainability

<b>BREEAM</b>	Contact Brett for more information
<b>BES 6001</b>	Contact Brett for more information
<b>Recyclable</b>	Contact Brett for more information
<b>Embodied Carbon</b>	Contact Brett for more information
<b>Brett 5-Star Sustainability Rating</b>	-

## Early Life and Maintenance

Once your paving has been installed, you may notice some changes to its appearance in the first few days and weeks. These visual changes can be due to a number of reasons originating from the concrete and/or the manufacturing or installation method.

Contact Brett for more information.