


# Decor 600x600mm Porcelain Paving Technical Data Sheet



Mosaic Grey



Mosaic Grey

## Description

The Decor Porcelain range consists of two striking designs that will be sure to inject a captivating feature into your garden design. The unique, muted accents of Mosaic Grey will add a truly romantic ambience to your outdoor space. The super chic Carrara Marble really is a statement piece and looks fantastic incorporated within outdoor kitchen and dining areas or swimming pool designs.

## Application

Decor Porcelain is designed for patio applications only.

<b>Product Type</b>	Dry-pressed ceramic tiles.
<b>Manufacturing Process</b>	Dry pressed and fired.
<b>Manufacturing Standard</b>	BS EN 14411:2016
<b>Design Standard</b>	-
<b>Installation Standard</b>	BS 7533-102: 2025
<b>UKCA/DOP</b>	Contact Brett for more information
<b>NBS Specification</b>	-

## Product Performance

Nominal Dimensions (mm)	Working Dimensions (mm)	No.per pack	m2 per pack	No.per m2	Pack wt max kg
600x600x20	600x600x20	16	5.86	2.73	266

<b>Tolerances</b>	Thickness $\pm 0.5\text{mm}$ Plan Size $\pm 0.6\%$ (Max $\pm 2\text{mm}$ )
<b>Breaking Strength</b>	Average Breaking Strength $\geq 10,000\text{ N}$
<b>Abrasion Resistance</b>	Class 4 – In accordance with EN ISO: 10545-7
<b>Staining Resistance</b>	Class 5 – In accordance with EN ISO: 10545-14
<b>Frost Resistance</b>	Pass – In accordance with EN ISO 10545-12
<b>Slip / Skid Resistance</b>	$>36$ (36+ Low Slipping Risk) R values are not recognised in the UK but are available on request
<b>Reaction to Fire</b>	Class A1 FL / A1
<b>Average Modulus of Rupture</b>	$\geq 35\text{ N/mm}^2$
<b>Water absorption</b>	$\leq 0.5\%$

## Sustainability

<b>BREEAM</b>	Contact Brett for more information
<b>BES 6001</b>	Contact Brett for more information
<b>Recyclable</b>	Contact Brett for more information
<b>Embodied Carbon</b>	Contact Brett for more information
<b>Brett 5-Star Sustainability Rating</b>	-

## Early Life and Maintenance

Once your paving has been installed, you may notice some changes to its appearance in the first few days and weeks. These visual changes can be due to a number of reasons originating from the concrete and/or the manufacturing or installation method.

Contact Brett for more information.